


Assembly Procedure : AP001

The assembly procedure is given on its own separate instruction sheet. Please request the above AP number.

Stripping Dimensions



- a = 4.0 mm
- b = 8.0 mm
- c = 16.0 mm
- d = 12.0 mm

BNC R/A PLUG CRIMP

10-104-AO-AI

Suitable for Cables:

RG59, URM104, URM70, RG62, KX6, KX52, KX30

Electrical Specification

Impedance: 75 Ohm
 Frequency: 0-1 GHz (Cable Limited)
 Dielectric W/V: 1500 Veff
 Insulation res: 5000 M-Ohm

Mechanical Specification

Centre contact retention
 Axial Force: 10 N min
 Cable Retention: 120 N min
 Mating cycles: 250
 Weight: g

Environmental Specification

Operating Temp: -30 to +70 Deg C.

Tooling

Centre Contact: Hex 1.72mm A/F
 Tool No: 336A
 Crimp Sleeve: Hex 6.50mm A/F
 Tool No: 336A

9	FERRULE	BRASS	NICKEL
8	CENTRE CONTACT	BRASS	GOLD
7	BODY	BRASS	NICKEL
6	WASHER	Fe	NICKEL
5	SPRING	SK5	NICKEL
4	INNER RETAINING RING	SK5	NICKEL
3	GASKET	SILICONE	N/A
2	INSULATOR	DELTRIN	N/A
1	BAYONET CAP	ZINC	NICKEL

ITEM	DESCRIPTION	MATERIAL	PLATING
A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETERS	
REVISION :	A03	NAME	SIGNATURE
ISSUE :	0	DATE	
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		DRAWN	IG
		CHK'D	GE
		APPV'D	
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.			



NAME	SIGNATURE	DATE
IG		05/01/2011
GE		11/01/2011

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.