

PRODUCT DATASHEET


10-32 STRAIGHT PCB JACK

54-452-D3



images for illustration purposes only

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD FARRY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT



4	GASKET		SILICONE		N/A	
3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		BeCu		GOLD	
1	BODY		BRASS		GOLD	
ITEM	DESCRIPTION		MATERIAL		PLATING	
Α4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00			NAME	SIGN	ATURE	DATE
		DRAWN	IG			04/07/2012
ISSUE	: 1	CHK'D	GE			18/07/2012
6-8 COLNE ROAD,		APPV'D				
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS				

□6

□0.9 X 4

SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS,WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR

Fax: +44(0)20 8538 9890

Assembly Procedure: Not Applicable

Tooling

Centre Contact: Solder Tool No: Solder

Crimp Sleeve: Not Applicable Tool No: Not Applicable

Alignment Tool: Not Applicable Extraction: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 65

Electrical Specification

Impedance: 50 Ohm Frequency: 0-2 GHz

Dielectric W/V: 1000 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 27 N min Cable Retention: N/A N min

Mating cycles: 250 Weight: 2.19 g

Connector Interface

Tel: +44(0)20 8538 9090

TWICKENHAM, MIDDLESEX.

TW1 4JR

Email: info@coax-connectors.com