


PRODUCT DATASHEET

MICRO BNC 50 OHM SOLDER

67-005-B3-HD



THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT




	6	WASHERS		SK5		NICKEL	
	5	OUTER BODY		BRASS		NICKEL	
	4	GASKET		SILICONE		N/A	
	3	INSULATOR		PTFE		N/A	
	2	CENTRE CONTACT		BERYLLIUM COPPER		GOLD	
	1	BODY		BRASS		NICKEL	
	ITEM	DESCRIPTION		MATER	RIAL PL		ATING
	A4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
2	REVISION: A03			NAME	SIGNATURE		DATE
			DRAWN	S.O'D.			28/07/2016
	ISSUE	: 1	CHK'D	G.E.			28/07/2016
2	6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D				
			THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR				

Suitable for Cables:

(HD) 0.047" CONFORMABLE CABLE

Stripping Dimensions



a = 4.0 mm $b = 8.0 \, mm$ c = 16.0 mm

d = 12.0 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP001

Tooling

Centre Contact: Solder Tool No: Solder

Crimp Sleeve: Not Applicable Tool No: Not Applicable

Extraction: 96-1132 Alignment Tool: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.


IP Rating (Mated): IP 64

Electrical Specification Mechanical Specification

Impedance: 50 Ohm Contact Retention: 10 N min Frequency: 0-6 GHz Cable Retention: 150 N min

Dielectric W/V: 1000 Veff Mating cycles: 500 Insulation res: 10000 M-Ohm Weight: 5.18 g

Connector Interface





Note - 50 and 75 ohm versions of Micro BNC connectors are not compatible and permanent damage to the connector may occur if mated.

Tel: +44(0)20 8538 9090 Fax: +44(0)20 8538 9890 Email: info@coax-connectors.com