


PRODUCT DATASHEET

BNC STRAIGHT CRIMP / CRIMP PLUG 10-005-B36-FK





7	WASHERS		SK5		NICKEL	
6	BAYONET CAP		ZINC		NICKEL	
5	GASKET		SILICONE		N/A	
4	CRIMP SLEEVE		BRASS		NICKEL	
3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		BRASS		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATERIAL		PLATING	
Α4	SHEET 1 OF 1	/	DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00		ROHS 2002/95/EC	NAME	SIGNATURE		DATE
		DRAWN	P.P.			02/10/19
ISSUE	: 1	CHK'D	G.E.			03/10/19
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX.		APPV'D				
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT				


SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS,WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR

Fax: +44(0)20 8538 9890

Suitable for Cables:

(FK) TACHII TCX-4CFWS

Stripping Dimensions



 $a = 4.0 \, mm$ $b = 8.0 \, \text{mm}$ c = 16.0 mm

d = 12.0 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP001

Tooling

Centre Contact: HEX 1.72 A/F Tool No: 96-HTS-75A

Crimp Sleeve: Hex 8.23mm A/F Tool No: 96-HTS-75A

Extraction: 96-2208 Alignment Tool: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.


IP Rating (Mated): IP 64

Electrical Specification Mechanical Specification

Impedance: 75 Ohm Contact Retention: 10 N min Frequency: 0 - 4.5 GHz Cable Retention: 200 N min

Dielectric W/V: 1500 Veff Mating cycles: 500 Insulation res: 5000 M-Ohm Weight: 10.83 g

Connector Interface



Tel: +44(0)20 8538 9090

TW1 4JR

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LTD. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD FARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT

Email: info@coax-connectors.com