

PRODUCT DATASHEET

BNC 4 HOLE FLANGE MOUNT SOLDER JACK


10-371-B3



images for illustration purposes only

2013. THIS DOCUMENT IS THE PROPERTY OF COAX CONNECTORS LID. REPRODUCTION OR COMMUNICATION IN ANY FORM TO A THIRD PARTY IS PROHIBITED WITHOUT PRIOR WRITTEN CONSENT

TW1 4JR



3	INSULATOR		PTFE		N/A	
2	CENTRE CONTACT		PHOSPHOR BRONZE		GOLD	
1	BODY		BRASS		NICKEL	
ITEM	DESCRIPTION		MATERIAL		PLATING	
A4	SHEET 1 OF 1		DIMENSIONS ARE IN MILLIMETRES			
REVISION: A00			NAME	SIGNATURE		DATE
		DRAWN	G.E.			25/05/2021
ISSUE	: 1	CHK'D	P.S.			25/05/2021
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		APPV'D				
		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR				

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): NONE

Electrical Specification

Impedance: 50 Ohm Frequency: 1 GHz

Dielectric W/V: 1500 Veff Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min Cable Retention: Not Applicable

Mating cycles: 250 Weight: 10.02 g

Connector Interface



Tel: +44(0)20 8538 9090 Fax: +44(0)20 8538 9890 Email: info@coax-connectors.com