



SMA RIGHT ANGLED SOLDER/SOLDER PLUG 30-108-1-DS3-HA




images for illustration purposes only



Suitable for Cables:

(HA) RG405 (0.085"), UT85

Stripping Dimensions



a = 4.0 mm

Tooling

Centre Contact: Solder

Crimp Sleeve: Solder

Alignment Tool: Not Applicable

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 54

Electrical Specification

Impedance: 50 Ohm

Frequency: 0 - 12 GHz

Dielectric W/V: 750 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 27 N min


Cable Retention: 90 N min

Mating cycles: 500

Weight: 4.12 g

Connector Interface

image for illustration purposes only



6	SCREW CAP	STAINLESS STEEL	GOLD
5	COUPLING NUT	STAINLESS STEEL	GOLD
4	GASKET	SILICONE	N/A
3	INSULATORS	PTFE	N/A
2	CENTRE CONTACT	BRASS	GOLD
1	BODY	STAINLESS STEEL	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION :	A01	NAME	SIGNATURE	DATE
ISSUE :	1	DRAWN	G.E.	29/06/2022
		CHK'D	P.S.	29/06/2022
		APPV'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.		